

Acrylic Flex 325 Air Handler

Specifications

January 2013

Construction: Single-ply acrylic coated polyester fabric hose reinforced with a spring steel wire helix & external PVC wearstrip

Product Features:

- * Ideal for moving large volumes of air in portable or permanent ventilation/exhaust systems
- * Wearstrip offers additional external abrasion & drag resistance
- * Great compressibility
- * Retractability allows for convenient storage & easy transport
- * Listed as UL 94V-0 flame retardant

Application: Air.

Temperature Range: - 20 F to + 325 F

Sizes I.D. (inches): 8, 10, 12, 14, 16, 18, 20, and 24 Inch I.D.
Custom sizes up to 52 Inch ID available

ID Tolerances: To 8 Inch: -0.00 to + 0.125 Inch
8 Inch and over: - 0.00 to + 0.250 Inch

Standard Length: 25 Feet

Standard Colors: Yellow with a black wearstrip

End Finish: Plain Cut (cuffs and belted end finishes available)

Markets: Air Ventilation, Blower Hose, Chiller, Confined Space Ventilation, Dehumidification, Fans and Blowers, Flame Retardant, Function Tent HVAC, Humidity Control, Laser Engraving, Pet Training Hose, Utility Blowers, Ventilation

Rubber-Cal, Inc.
620 West Warner Ave
Santa Ana, CA 92707
800-370-9152

www.ducting.com



Acrylic Flex 325 Air Handler

Specifications

January 2013


Size Inside Diameter (Inches)	Approximate Weight Lbs./ft.	Min Centerline Bend Radius (Inches)	Compression Ratio	Max Recommended Negative Pressure (IN./HG)	Max Recommended Positive Pressure (PSI)
8	0.4	5	10 to 1		3
10	0.6	6	10 to 1		2
12	0.7	7.5	10 to 1		1.5
14	0.8	8.5	10 to 1		1.2
16	0.9	9.5	10 to 1		1
18	1.1	10.5	10 to 1		0.8
20	1.2	11.5	10 to 1		0.7
24	1.4	14	10 to 1		0.5

Note: Technical data based on 2 ft. straight lengths of hose 72 F.

Disclaimer: The proper use and maintenance of the hose and/or duct is the sole responsibility of the purchaser and ultimate user of the product. This information is presented as a general guide only. The number of variables which can be present in any application make firm recommendations impossible. Adequate testing under actual service conditions is necessary to properly establish suitability. We take pride in the quality of all of our products and we welcome comments and suggestions from our customers.

Rubber-Cal, Inc.
620 West Warner Ave
Santa Ana, CA 92707
800-370-9152

www.ducting.com



Ducting
.com