

# Klear Flex

Specifications

January 2013

**Construction:** Heavy weight black or clear polyurethane wall hose construction reinforced with a coated spring steel wire helix. Three inch black polyurethane cuffs ion each end of the hose.

Available in 2 versions HD and MD.

Klear-Flex HD Wall Thickness: .045 Inch

Klear-Flex MD Wall Thickness: .035 Inch

## Product Features:

- \* All Size are generally in stock and ship in 24hours.
- \* Excellent compressibility
- \* Offers maximum combination of flexibility and abrasion resistance
- \* Cut, gouge, and chemical resistant
- \* Efficient flow characteristics
- \* Designed for wide temperature ranges

**Applications:** Recommended for Street Sweeping Machines: Elgin, Jonhston, Schwarze, Supervac, Tymco

**Temperature Range:** - 65 F to + 225 F

**Sizes I.D. (inches):** 10-inch and 12inch ID

All ID Sizes are in stock and ship in 24 hours.

**ID Tolerances:** -0.00 to + 0.125 Inch

**Standard Length:** Custom Lengths

**Standard Colors:** Clear with a Black PU Cuff

**End Finish:** Cuffed Ends

**Markets:** Commercial Street Sweeper Machines

Rubber-Cal, Inc.  
620 West Warner Ave  
Santa Ana, CA 92707  
800-370-9152

[www.ducting.com](http://www.ducting.com)



**Ducting**  
**.com**