

Silico-550 Double Ply

Specifications

January 2013

Construction: Double-ply silicone coated fiberglass fabric hose reinforced with a spring steel wire helix & external filament fiberglass cord.

Product Features:

- * Suited for high temperature air handling applications
- * Ideal for plastic processing applications
- * Non-kinking
- * Narrow pitch allows for tight bending radius while maintaining a smooth air flow
- * Resistant to many oils and solvents, ozone, water, fungus, and alkalis
- * Not recommended for continuous flexing
- * Designed for both high and low temperature extremes

Applications: Air, Fume.

Temperature Range: - 65 F to + 550 F, Intermittent to 600F

Sizes I.D. (inches): 1, 1.25, 1.5, 1.75, 2, 2.25, 2.5, 3, 3.5, 4, 4.5, 5, 6, 8, 10 and 12

ID Tolerances: -0.00 to + 0.125 Inch

Standard Length: 12 Feet

Standard Colors: Iron Oxide Red

End Finish: Plain Cut (cuffs available)

Markets: Aircraft, Automotive, Brake Ducting, Brick Kilns, Cab Ventilation, Defroster/Heater Hose, Dry Cleaning, Dryer Hose, Exhaust Systems, Foundries, Garage Exhaust, Heater, Glass Drying, High Temperature Applications, Paper Mills, Plastics Industry, Rocket Support Duct, Tractor Pull Exhaust, Transmission Cooling, Vehicle Exhaust Systems

Rubber-Cal, Inc.
620 West Warner Ave
Santa Ana, CA 92707
800-370-9152

www.ducting.com



Ducting
.com

Silico-550 Double Ply

Specifications

January 2013

Size Inside Diameter (Inches)	Approximate Weight Lbs./ft.	Min Centerline Bend Radius (Inches)	Compression Ratio	Max Recommended	
				Negative Pressure (IN./HG)	Positive Pressure (PSI)
1	0.12	1.2	3 to 1	29	30
1.5	0.17	1.8	3.7 to 1	29	30
2	0.25	2	3.7 to 1	29	30
2.5	0.3	2.3	3.7 to 1	29	30
3	0.33	2.5	3.7 to 1	29	30
3.5	0.4	2.5	3.7 to 1	29	30
4	0.48	3	4.8 to 1	27	30
4.5	0.54	3.2	4.8 to 1	20	30
5	0.59	3.5	4.8 to 1	14	30
6	0.62	4	6 to 1	9	19
8	0.79	4	6 to 1	9	14
10	0.98	5	6 to 1	1	11
12	1.2	5	6 to 1	0.6	9.4

Note: Technical data based on 2 ft. straight lengths of hose 72 F.

Disclaimer: The proper use and maintenance of the hose and/or duct is the sole responsibility of the purchaser and ultimate user of the product. This information is presented as a general guide only. The number of variables which can be present in any application make firm recommendations impossible. Adequate testing under actual service conditions is necessary to properly establish suitability. We take pride in the quality of all of our products and we welcome comments and suggestions from our customers.

Rubber-Cal, Inc.
620 West Warner Ave
Santa Ana, CA 92707
800-370-9152
www.ducting.com

