

Silico-550 Single Ply

Specifications

January 2013

Construction: Single-ply silicone coated fiberglass fabric hose reinforced with a spring steel wire helix & external filament cord..

Product Features:

- * Suited for high temperature air handling applications
- * The narrow pitch allows for tight bending radius while maintaining a smooth air flow
- * Non-kinking
- * Resistant to many oils and solvents, ozone, water, fungus, and alkalis
- * Not recommended for continuous flexing

Applications: Air, Fume.

Temperature Range: - 65 F to + 500 F

Sizes I.D. (inches): 1, 1.5, 2, 2.5, 3, 3.5, 4, 4.5, 5, 6 and 8

ID Tolerances: -0.00 to + 0.125 Inch

Standard Length: 12 Feet

Standard Colors: Iron Oxide Red

End Finish: Plain Cut (cuffs available)

Markets: Aircraft, Automotive, Brake Ducting, Brick Kilns, Cab Ventilation, Defroster/Heater Hose, Dryer Hose, Dry Cleaning Hose, Heater, High Temperature Application, Paper Mills, Plastics Industry, Transmission Cooling

Rubber-Cal, Inc.
620 West Warner Ave
Santa Ana, CA 92707
800-370-9152

www.ducting.com



Ducting
.com

Silico-550 Single Ply

Specifications

January 2013

Size Inside Diameter (Inches)	Approximate Weight Lbs./ft.	Min Centerline Bend Radius (Inches)	Compression Ratio	Max Recommended Negative Pressure (IN./HG)	Max Recommended Positive Pressure (PSI)
1	0.12	1.2	3 to 1	29	30
1.5	0.15	1.5	3 to 1	29	30
2	0.19	2	3 to 1	29	30
2.5	0.24	2.375	3 to 1	29	30
3	0.28	3	3 to 1	22	30
4	0.39	3.4	3.5 to 1	19	27
4.5	0.44	3.7	3.5 to 1	13	25
5	0.49	4.1	3.5 to 1	7	21
6	0.52	4.4	4.5 to 1	4	13

Note: Technical data based on 2 ft. straight lengths of hose 72 F.

Disclaimer: The proper use and maintenance of the hose and/or duct is the sole responsibility of the purchaser and ultimate user of the product. This information is presented as a general guide only. The number of variables which can be present in any application make firm recommendations impossible. Adequate testing under actual service conditions is necessary to properly establish suitability. We take pride in the quality of all of our products and we welcome comments and suggestions from our customers.

Rubber-Cal, Inc.
620 West Warner Ave
Santa Ana, CA 92707
800-370-9152
www.ducting.com

