

# Speed-Flex 625

Specifications

January 2013

**Construction:** Lightweight laminate of fiberglass and vacuum metalized polyester film.

**Product Features:**

- \* Heat reflective
- \* Lightweight and flexible
- \* Smooth bend radius
- \* Heat reflective to 625F
- \* 2.64-inch compression per foot of hose
- \* Designed for brake ducting and ventilation of drive compartments in racecars

**Applications:** Air, Fume.

**Temperature Range:** - 65 F to + 625 F

**Sizes I.D. (inches):** 1.50, 2.00, 2.50, and 3.00, Custom sizes to 8 inch ID

**ID Tolerances:** -0.00 to + 0.125 Inch

**Standard Length:** 12 Feet

**Standard Colors:** Silver

**End Finish:** Plain Cut

**Markets:** Aerospace, Brake Ducting, Cab Ventilation, Paper Mills, Plastics Industry, Transmission Cooling

Rubber-Cal, Inc.  
620 West Warner Ave  
Santa Ana, CA 92707  
800-370-9152

[www.ducting.com](http://www.ducting.com)



**Ducting**  
**.com**

# Speed-Flex 625

Specifications

January 2013

Size Inside Diameter (Inches)	Approximate Weight Lbs./ft.	Min Centerline Bend Radius (Inches)	Compression Ratio	Max Recommended	Max Recommended
				Negative Pressure (IN./HG)	Positive Pressure (PSI)
1.5	0.18	1.13	3 to 1	29	30
2	0.25	1.58	3 to 1	29	30
3	0.319	2.375	4 to 1	29	30

Note: Technical data based on 2 ft. straight lengths of hose 72 F.

**Disclaimer:** The proper use and maintenance of the hose and/or duct is the sole responsibility of the purchaser and ultimate user of the product. This information is presented as a general guide only. The number of variables which can be present in any application make firm recommendations impossible. Adequate testing under actual service conditions is necessary to properly establish suitability. We take pride in the quality of all of our products and we welcome comments and suggestions from our customers.

Rubber-Cal, Inc.  
620 West Warner Ave  
Santa Ana, CA 92707  
800-370-9152

[www.ducting.com](http://www.ducting.com)



**Ducting**  
.com